

View Online at <https://aerobasegroup.com/nsn/5930-00-966-7705>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.218 inches

Overall Height:

1.000 inches

Overall Width:

0.814 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.250 inches single actuator

Nonturn Device Radius:

0.375 inches at 12: 00 o'clock

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-60.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section front

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

4 each section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop-breakoff tab single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0