

View Online at <https://aerobasegroup.com/nsn/5930-00-968-3253>

Thread Class:

2a single mounting facility

Thread Length:

0.344 inches single mounting facility

Overall Length:

6.156 inches

Overall Height:

1.875 inches

Overall Width:

1.516 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.281 inches single actuator

Overall Diameter:

1.875 inches

Nonturn Device Radius:

0.500 inches at 3: 00 o'clock

Individual Section Quantity:

9

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

4 4th section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

150.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0