

View Online at <https://aerobasegroup.com/nsn/5930-00-969-1048>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.950 inches

**Unthreaded Mounting Hole Diameter:**

0.139 inches

**Actuator Length:**

0.967 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.422 inches

**Actuator Roller Diameter:**

0.370 inches

**Actuator Roller Width:**

0.150 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**End Application:**

Wiwo jima class lph; aircraft, hornet f/a-18; victorious class t-agos 19; yellowstone class ad-41; laundry equipment; deck machinery; john macdonald class tags-51; impeccable class t-agos 23; pave tack system; aircraft, tomcat f-14

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.5 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

Between 0.250 pretravel inches and 0.031 overtravel inches and 0.045 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0