NSN 5930-00-969-1963

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-969-1963

Body Style:

Hole mounted

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.350 inches

Unthreaded Mounting Hole Diameter:

0.152 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.050 inches

Actuator Free Position Height:

Between 0.625 inches and 0.655 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Switch Release Force:

10.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

Between 0.050 pretravel millimeters and 0.010 overtravel millimeters and 0.007 differential millimeters

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

NSN 5930-00-969-1963

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

