NSN 5930-00-969-2187

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-969-2187

Overall Length:
5.000 inches
Overall Height:
5.562 inches
Overall Width:
2.688 inches
Body Length:
4.782 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
6.000 inches
Bulb Diameter:
1.125 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
rempurature sensing Element Type.
Capillary tube-bulb
Capillary tube-bulb
Capillary tube-bulb Mounting Method:
Capillary tube-bulb Mounting Method: Bracket
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point not adjustable and actuation point adjustable
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point not adjustable and actuation point adjustable Contact Adjustment Range:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point not adjustable and actuation point adjustable Contact Adjustment Range: +25.00/+90.00 actuation point degrees fahrenheit
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point not adjustable and actuation point adjustable Contact Adjustment Range: +25.00/+90.00 actuation point degrees fahrenheit Contact Adjustment Type:
Capillary tube-bulb Mounting Method: Bracket Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, both positions maintained Terminal Type: Tab w/screw Contact Load Current Rating: 9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point not adjustable and actuation point adjustable Contact Adjustment Range: +25.00/+90.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw

60.0 single voltage

NSN 5930-00-969-2187

Thermostatic Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0