

View Online at <https://aerobasegroup.com/nsn/5930-00-969-5707>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.750 inches

Overall Diameter:

2.300 inches

Pressure Switch Type:

Gage

Mounting Method:

Bushing

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Adjustment Range:

+5.40/+6.60 actuation point pounds per square inch gage

Contact Stimulus Rating:

50.00 actuation point pounds per square inch and 30.00 deactuation point pounds per square inch and 20.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

440.0 ac at sea level single voltage

Pressure Connector Type:

Compression, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0