

View Online at <https://aerobasegroup.com/nsn/5930-00-969-5707>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.750 inches

**Overall Diameter:**

2.300 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bushing

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Adjustment Range:**

+5.40/+6.60 actuation point pounds per square inch gage

**Contact Stimulus Rating:**

50.00 actuation point pounds per square inch and 30.00 deactuation point pounds per square inch and 20.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

440.0 ac at sea level single voltage

**Pressure Connector Type:**

Compression, threaded external single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0