

View Online at <https://aerobasegroup.com/nsn/5930-00-969-6837>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture proof

Bushing Length:

0.469 inches

Body Length:

0.840 inches

Body Width:

0.719 inches

Body Height:

0.978 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

0.938 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and center position no locking action

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Uninclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0