

View Online at <https://aerobasegroup.com/nsn/5930-00-970-6508>

Thread Length:

0.430 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.900 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.380 inches single actuator

Overall Diameter:

1.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 single section front

Throw Quantity:

16 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

202.5 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+1.000/+3.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0