

View Online at <https://aerobasegroup.com/nsn/5930-00-971-2099>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

Between 1.657 inches and 1.719 inches

Body Diameter:

Between 0.641 inches and 0.671 inches

Bushing Length:

Between 0.297 inches and 0.327 inches

Body Length:

Between 0.767 inches and 0.797 inches

Case Material:

Metal

Actuator Diameter:

Between 0.344 inches and 0.406 inches

Actuator Height:

Between 0.219 inches and 0.281 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc

Test Data Document:

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0