

View Online at <https://aerobasegroup.com/nsn/5930-00-971-2099>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

Between 1.657 inches and 1.719 inches

**Body Diameter:**

Between 0.641 inches and 0.671 inches

**Bushing Length:**

Between 0.297 inches and 0.327 inches

**Body Length:**

Between 0.767 inches and 0.797 inches

**Case Material:**

Metal

**Actuator Diameter:**

Between 0.344 inches and 0.406 inches

**Actuator Height:**

Between 0.219 inches and 0.281 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc

**Test Data Document:**

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0