

View Online at <https://aerobasegroup.com/nsn/5930-00-972-2866>

Hazardous Locations/environmental Protection:

Submersible

Actuator Style:

Round

Actuator Diameter:

Between 0.370 inches and 0.380 inches

Actuator Height:

Between 1.657 inches and 1.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

175.000 amperes resistive dc and 45.000 amperes inductive dc and 35.000 amperes lamp dc and 55.000 amperes resistive ac and 45.000 amperes inductive ac and 11.000 amperes lamp ac

Test Data Document:

81349-mils3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0