

View Online at <https://aerobasegroup.com/nsn/5930-00-972-3159>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

Between 5.572 inches and 5.602 inches

Overall Height:

2.317 inches

Overall Width:

1.973 inches

First Flat Length:

0.359 inches single actuator and 0.391 inches single actuator

Flat Height:

0.217 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.922 inches single actuator and 0.952 inches single actuator

Nonturn Device Radius:

0.515 inches at 10: 30 o'clock and 0.547 inches at 10: 30 o'clock

Individual Section Quantity:

12

Nonturn Device Type:

Tab at 10: 30 o'clock

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0