

View Online at <https://aerobasegroup.com/nsn/5930-00-972-3350>

Thread Class:

3b single pressure connection

Overall Length:

5.125 inches

Overall Width:

3.312 inches

Body Diameter:

3.469 inches

Body Length:

2.750 inches

Longest Horizontal Distance Between Mounting Centers:

2.562 inches

Longest Vertical Distance Between Mounting Centers:

2.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+1.90/+95.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

0.25 deactuation point pounds per square inch and 1.65 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0