NSN 5930-00-972-9571

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-972-9571

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Body Length:
2.250 inches
Body Width:
1.750 inches
Body Height:
1.625 inches
Switch Actuator Quantity:
1
Actuator Height:
0.312 inches
Maximum Voltage Rating In Volts:
440.0 ac and 440.0 dc
Inclosure Type:
Uninclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.404 in the
0.164 inches
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 5.000 amperes resistive ac Special Features: 4 mtg screws Thread Series Designator: Unc Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: