NSN 5930-00-973-5769

Hazardous Locations/environmental Protection:

Watertight

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-973-5769

Overall Length:
5.000 inches
Overall Height:
5.688 inches
Overall Width:
2.688 inches
Capillary Tube Length:
180.000 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
130.0 degrees fahrenheit
Mounting Method:
Bracket
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Tab w/screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+25.00/+90.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Frequency In Hertz:
60.0 single voltage

NSN 5930-00-973-5769

Thermostatic Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0