NSN 5930-00-974-5552

Sensitive Switch - Page 1 of 2

Between 0.998 inches and 1.002 inches

Body Style: Hole mounted Overall Length: 2.437 inches

Overall Width: 0.687 inches



View Online at https://aerobasegroup.com/nsn/5930-00-974-5552

Center To Center Distance Between Mounting Facilities Parallel To Length:

Body Length:
Between 1.922 inches and 1.952 inches
Body Width:
Between 0.672 inches and 0.702 inches
Body Height:
0.984 inches
Case Material:
Plastic
Actuator Length:
1.968 inches
Actuator Style:
Leaf
Actuator Width:
0.219 inches
Actuator Free Position Height:
Between 0.697 inches and 0.813 inches
Actuator Adapter Style:
Leaf
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
3.0 ounces

NSN 5930-00-974-5552

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.375 pretravel inches and 0.160 overtravel inches and 0.060 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Thread Series Designator	Thread	Series	Design	ator
--------------------------	--------	---------------	--------	------

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0