NSN 5930-00-974-5628

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-974-5628

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.870 inches and 0.880 inches
Body Length:
1.094 inches
Body Width:
Between 0.172 inches and 0.204 inches
Body Height:
Between 0.609 inches and 0.641 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.401 inches and 0.411 inches
Actuator Style:
Leaf
Actuator Width:
0.115 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Threaded hole Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Actuating Force: 8.0 ounces Actuator Movement: Between 0.187 pretravel inches and 0.062 overtravel inches and 0.078 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: