

View Online at <https://aerobasegroup.com/nsn/5930-00-974-5646>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Salt spray resistant

Bushing Length:

Between 0.178 inches and 0.198 inches

Body Length:

Between 0.355 inches and 0.385 inches

Body Width:

Between 0.365 inches and 0.385 inches

Case Material:

Plastic

Actuator Diameter:

Between 0.552 inches and 0.572 inches

Actuator Height:

Between 0.446 inches and 0.496 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc

Test Data Document:

13499-c266-7093-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0