Mounting Facility Pattern:

Four position rectangular single mounting facility



NSN 5930-00-974-7861 Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-974-7861
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
6.718 inches
Overall Height:
6.000 inches
Overall Width:
4.750 inches
First Flat Length:
1.125 inches single actuator
Flat Height:
0.281 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.438 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
3.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
2 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
450.0 ac at sea level

NSN 5930-00-974-7861

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

--

Fiig:

A052b0