# NSN 5930-00-974-9932

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-974-9932

## **Inside Diameter:**

0.250 inches single connection

## Hazardous Locations/environmental Protection:

Watertight

# **Overall Length:**

5.875 inches

## **Overall Height:**

7.187 inches

#### **Overall Width:**

2.812 inches

#### **Body Height:**

2.750 inches

## **Unthreaded Mounting Hole Diameter:**

#### 0.281 inches

## Longest Horizontal Distance Between Mounting Centers:

2.406 inches

## Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

# Longest Vertical Distance Between Mounting Centers:

3.281 inches

# Pressure Switch Type:

Absolute

#### **Mounting Method:**

Bracket and unthreaded hole

## **Features Provided:**

Electrical access port

#### **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

20.00 pounds per square inch gage

#### **Thread Size:**

0.250 inches single pressure connection

#### **Mounting Facility Pattern:**

Isosceles triangle

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

## **Terminal Type:**

Screw

#### **Contact Load Current Rating:**

16.0 amperes inductive load first voltage8.0 amperes inductive load second voltage4.0 amperes inductive load third voltage3.2 amperes inductive load fourth voltage9.6 amperes inductive load fifth voltage4.8 amperes inductive load sixth voltage2.5 amperes inductive load seventh voltage2.0 amperes inductive load eighth voltage

#### **Contact Adjustability:**

Actuation point not adjustable

# NSN 5930-00-974-9932

Pressure Switch - Page 2 of 2



## **Contact Stimulus Rating:**

-1.08 actuation point pounds per square inch absolute and -4.91 actuation point pounds per square inch absolute

# **Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage550.0 ac at sea level fourth

voltage115.0 dc at sea level fifth voltage230.0 dc at sea level sixth voltage440.0 dc at sea level seventh voltage550.0 dc at sea level eighth voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A048b0