

View Online at <https://aerobasegroup.com/nsn/5930-00-975-3574>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.150 inches

Body Diameter:

1.560 inches

Overall Diameter:

1.870 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Outlet connection

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

250.00 pounds per square inch

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.00 actuation point pounds per square inch gage and 17.00 deactuation point pounds per square inch gage and 2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 second voltage and 60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0