

View Online at <https://aerobasegroup.com/nsn/5930-00-975-3575>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

4.150 inches

Overall Height:

1.870 inches

Overall Width:

1.870 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -34.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Input port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

100.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

21.00 actuation point pounds per square inch gage and 21.42 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Pressure Connector Type:

Flareless, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0