

View Online at <https://aerobasegroup.com/nsn/5930-00-975-7707>

Body Style:

Hole mounted

Overall Length:

2.469 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Width:

0.687 inches

Body Length:

Between 1.522 inches and 1.952 inches

Body Width:

Between 0.672 inches and 0.702 inches

Body Height:

0.984 inches

Case Material:

Plastic

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.124 inches and 1.250 inches

Actuator Roller Diameter:

Between 0.360 inches and 0.390 inches

Actuator Roller Width:

Between 0.135 inches and 0.165 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

3.0 ounces

Actuator Movement:

Between 0.281 pretravel inches and 0.156 overtravel inches and 0.080 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes resistive ac and 1.500 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0