# NSN 5930-00-975-9629

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-975-9629

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

4.199 inches

#### **Overall Height:**

1.875 inches

**Overall Width:** 

1.609 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.875 inches single actuator

# Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

# Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

#### **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

10 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-975-9629

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

### Precious Material And Location:

Clips and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

# Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A052b0