

View Online at <https://aerobasegroup.com/nsn/5930-00-975-9636>

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.622 inches

Overall Height:

1.875 inches

Overall Width:

1.609 inches

First Flat Length:

0.281 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.750 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round, flatted single actuator

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0