

View Online at <https://aerobasegroup.com/nsn/5930-00-976-9290>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Width Between Flats:

0.186 inches single actuator

Overall Length:

2.063 inches

Overall Height:

1.016 inches

Overall Width:

0.938 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.287 inches single actuator

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0