# NSN 5930-00-977-1153

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-977-1153

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

10.718 inches

#### **Overall Height:**

1.531 inches

#### **Overall Width:**

1.375 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.312 inches single actuator

#### **Nonturn Device Radius:**

0.531 inches at 10: 00 o'clock

# Individual Section Quantity:

5

Nonturn Device Type:

Tab at 10: 00 o'clock

# **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

6 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

# NSN 5930-00-977-1153

Rotary Switch - Page 2 of 2



**Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0