

View Online at <https://aerobasegroup.com/nsn/5930-00-977-1760>

**Body Style:**

Hole mounted

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.125 inches

**Overall Height:**

0.593 inches

**Overall Width:**

0.531 inches

**Body Length:**

0.875 inches

**Body Width:**

0.531 inches

**Body Height:**

0.281 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

0.156 inches

**Actuator Height:**

0.031 inches

**Actuator Width:**

0.062 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**End Application:**

Spruance class d (963), virginia class cgn(41), sturgeon class ssn(637), los angeles class ssn(688), ticonderoga class cg(47), kidd class ddg, interrogator set(a0681)(an/upx-27) , nimitz class cvn, forrestal class cv

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 3.000 amperes resistive ac

**Special Features:**

Weapons system essential

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0