

View Online at <https://aerobasegroup.com/nsn/5930-00-977-1760>

Body Style:

Hole mounted

Overall Length:

1.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.125 inches

Overall Height:

0.593 inches

Overall Width:

0.531 inches

Body Length:

0.875 inches

Body Width:

0.531 inches

Body Height:

0.281 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

0.156 inches

Actuator Height:

0.031 inches

Actuator Width:

0.062 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

End Application:

Spruance class d (963), virginia class cgn(41), sturgeon class ssn(637), los angeles class ssn(688), ticonderoga class cg(47), kidd class ddg, interrogator set(a0681)(an/upx-27) , nimitz class cvn, forrestal class cv

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 3.000 amperes resistive ac

Special Features:

Weapons system essential

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0