

View Online at <https://aerobasegroup.com/nsn/5930-00-977-2680>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.719 inches

Body Height:

0.884 inches

Actuator Style:

Rectangular

Actuator Height:

0.640 inches

Actuator Width:

0.225 inches

Actuator Position-action Relationship:

Center position maintained and left position momentary and right position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0