

View Online at <https://aerobasegroup.com/nsn/5930-00-977-9389>

Overall Length:

3.790 inches

Overall Height:

1.250 inches

Overall Width:

2.250 inches

Unthreaded Mounting Hole Diameter:

0.205 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.484 inches and 1.516 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.422 inches and 0.454 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Features Provided:

Tamper proof cap

Contact Action Stimulus:

Increase

Proof Pressure:

5000.00 pounds per square inch

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+10.00/+200.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Frequency In Hertz:

400.0 second voltage

Media For Which Designed:

Liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0