

View Online at <https://aerobasegroup.com/nsn/5930-00-977-9389>

**Overall Length:**

3.790 inches

**Overall Height:**

1.250 inches

**Overall Width:**

2.250 inches

**Unthreaded Mounting Hole Diameter:**

0.205 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 1.484 inches and 1.516 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.422 inches and 0.454 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Tamper proof cap

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

5000.00 pounds per square inch

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+10.00/+200.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

28.0 dc at sea level third voltage

**Frequency In Hertz:**

400.0 second voltage

**Media For Which Designed:**

Liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0