

View Online at <https://aerobasegroup.com/nsn/5930-00-978-6907>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.190 inches single pressure connection

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant

Overall Length:

3.410 inches

Body Length:

2.145 inches

Overall Diameter:

Between 1.230 inches and 1.280 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.657 inches and 0.719 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 95.0 degrees celsius

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

600.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

39.00 actuation point pounds per square inch and 45.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0