NSN 5930-00-978-9008

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-978-9008

Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.110 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
1.938 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.188 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.156 inches
Maximum Voltage Rating In Volts:
230.0 ac
End Application:
Nuclear power plants.
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.7 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
3.5 ounces

NSN 5930-00-978-9008

Sensitive Switch - Page 2 of 2



Δ	cti	Jato	r N	lov	em	en	ŧ.
м	CLI	uaic	JI IV	w	em		ш.

Between 0.218 pretravel inches and 0.156 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0