# NSN 5930-00-978-9699

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-978-9699

| Body Style:  |
|--|
| Bushing mount  |
| Hazardous Locations/environmental Protection:                                      |
| Weatherproof   |
| Overall Length:  |
| 1.336 inches   |
| Overall Height:  |
| 2.593 inches   |
| Overall Width:   |
| 1.015 inches   |
| Bushing Length:  |
| 0.469 inches   |
| Body Length:   |
| 1.336 inches   |
| Body Width:  |
| 1.015 inches   |
| Case Material:   |
| Plastic  |
| Actuator Style:  |
| Round  |
| Actuator Diameter:   |
| 0.430 inches   |
| Actuator Height:   |
| 0.921 inches   |
| Actuator Position-action Relationship:   |
| Up position maintained and down position maintained and center position maintained |
| Actuator Position-locking Relationship:  |
| Up position locked in and down position locked in and center position locked in    |
| Actuator Color:  |
| Natural single actuator  |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Mounting Surface To Terminal End Distance:   |
| 1.203 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing   |
| Features Provided:   |
| Actuator seal  |
| Thready Qty Per Inch (tpi):  |

32

# NSN 5930-00-978-9699

Toggle Switch - Page 2 of 2



| Т | h | rea | d | Si | 76 |  |
|---|---|-----|---|----|----|--|
|   |   |     |   |    |    |  |

0.469 inches

# **Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

# **Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

#### **Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Uns

# **Terminal Type And Quantity:**

6 tab w/screw

# **Specification Data:**

96906-ms24613 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0