

View Online at <https://aerobasegroup.com/nsn/5930-00-981-1770>

Body Style:

Hole mounted

Overall Length:

1.937 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Width:

0.687 inches

Body Length:

Between 1.922 inches and 1.952 inches

Body Width:

Between 0.672 inches and 0.702 inches

Body Height:

0.984 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.219 inches

Actuator Free Position Height:

Between 0.605 inches and 0.645 inches

Actuator Adapter Style:

Pushbutton

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.005 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0