## NSN 5930-00-981-1770

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-981-1770

1.937 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Width:
0.687 inches
Body Length:
Between 1.922 inches and 1.952 inches
Body Width:
Between 0.672 inches and 0.702 inches
Body Height:
0.984 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.219 inches
Actuator Free Position Height:
Between 0.605 inches and 0.645 inches
Actuator Adapter Style:
Pushbutton
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.005 overtravel inches and 0.003 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000
amperes inductive ac and 1.500 amperes lamp ac

## NSN 5930-00-981-1770

Sensitive Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0