

View Online at <https://aerobasegroup.com/nsn/5930-00-981-2776>

**Body Style:**

Hole mounted

**Overall Length:**

0.510 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.364 inches and 0.384 inches

**Overall Width:**

0.200 inches

**Body Length:**

0.510 inches

**Body Width:**

Between 0.190 inches and 0.210 inches

**Body Height:**

Between 0.340 inches and 0.360 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Free Position Height:**

Between 0.305 inches and 0.335 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.010 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0