

View Online at <https://aerobasegroup.com/nsn/5930-00-981-2776>

Body Style:

Hole mounted

Overall Length:

0.510 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.364 inches and 0.384 inches

Overall Width:

0.200 inches

Body Length:

0.510 inches

Body Width:

Between 0.190 inches and 0.210 inches

Body Height:

Between 0.340 inches and 0.360 inches

Unthreaded Mounting Hole Diameter:

0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.087 inches and 0.090 inches

Actuator Free Position Height:

Between 0.305 inches and 0.335 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.010 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0