

View Online at <https://aerobasegroup.com/nsn/5930-00-981-9631>

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant

Overall Length:

1.224 inches

Overall Height:

0.500 inches

Body Diameter:

0.572 centimeters

Mounting Slot Width:

Between 0.133 inches and 0.147 inches

Body Height:

0.315 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Longest Horizontal Distance Between Mounting Centers:

Between 0.930 inches and 0.944 inches

Temperature Sensing Element Type:

Disc

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

390.00 actuation point degrees fahrenheit and 410.00 actuation point degrees fahrenheit and 340.00 deactuation point degrees fahrenheit and 360.00 deactuation point degrees fahrenheit and 50.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0