NSN 5930-00-982-1425

Switch Box - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-982-1425 |
|---|
| Hazardous Locations/environmental Protection: |
| General purpose-nema type 1 |
| Overall Depth: |
| 6.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 8.500 inches |
| Overall Height: |
| 15.875 inches |
| Overall Width: |
| 11.375 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 13.750 inches |
| Standard Mounting Pattern Designator: |
| 4 point-rectangular |
| Entrance Diameter Numeric Designator: |
| 0.750/1.000/1.250 |
| Cable Entrance Diameter: |
| 1.000 inches |
| System For Which Designed: |
| Four wire three phase |
| Cable Opening Length: |
| 1.250 inches |
| Cable Opening Width: |
| 0.750 inches |
| Mounting Method: |
| Unthreaded hole |
| Locking Device Type: |
| Padlock |
| Main Line Maximum Current Rating In Amps: |
| 30.0 |
| Main Line Maximum Ac Voltage Rating In Volts: |
| 480.0 |
| Ground Connection Type For Which Designed: |
| Fusible |
| Switch Type And Quantity: |
| 1 knife |
| Entrance Type And Quantity: |
| 4 triple concentric knockout |

Material:

Steel

NSN 5930-00-982-1425 Switch Box - Page 2 of 2

A17600



| Surface Treatment: |
|--|
| Enamel |
| Style Designator: |
| Rectangular, surface mounting |
| Test Data Document: |
| 81348-ws865 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Or Standard: |
| Hd type and 3 class and 3sn design and 1 box |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |