

View Online at <https://aerobasegroup.com/nsn/5930-00-982-5972>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Overall Length:**

Between 7.328 inches and 7.422 inches

**Overall Height:**

2.250 inches

**Overall Width:**

2.250 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.969 inches single actuator and 1.031 inches single actuator

**Nonturn Device Radius:**

0.484 inches at 1:00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 1:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

24 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0