## NSN 5930-00-982-7799

Sensitive Switch - Page 1 of 2

**Overall Length:** 

Unef



View Online at https://aerobasegroup.com/nsn/5930-00-982-7799

4.500 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Diameter:
1.000 inches
Bushing Length:
0.812 inches
Body Length:
2.907 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
0.781 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.120 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
1.000 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:
Between 92.0 ounces and 192.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac
Thread Series Designator:

## NSN 5930-00-982-7799

Sensitive Switch - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0