

View Online at <https://aerobasegroup.com/nsn/5930-00-982-8382>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.312 inches 1st mounting facility

**Overall Length:**

6.147 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Individual Section Quantity:**

7

**Longest Horizontal Distance Between Mounting Centers:**

1.375 inches 2nd mounting facility

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+0.500/+50.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

4.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0