

View Online at <https://aerobasegroup.com/nsn/5930-00-984-1101>

Body Style:

Bushing mounted

Body Diameter:

0.437 inches

Bushing Length:

0.250 inches

Body Length:

0.703 inches

Case Material:

Metal

Actuator Diameter:

0.128 inches

Actuator Height:

0.187 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Ticroderoga class c (47), sturgeon class ssn(637), defense meteorological satellite program(dmsp), emory s. Land class as, deep submergence systems programs(dssp), harpoon(agm-84) anti-ship all weather missile, tarawa class lha, phoenix(aim-54) air to air missile, los angeles class ssn(688) .

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 500.000 milliamperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminals silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0