NSN 5930-00-984-5352

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:

Industrial use
Overall Length:
1.430 inches
Overall Height:
0.870 inches
Overall Width:
0.870 inches

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-00-984-5352

Body Diameter:
0.500 inches
Bushing Length:
0.310 inches
Body Length:
0.420 inches
Case Material:
Metal
Actuator Diameter:
0.370 inches
Actuator Height:
0.310 inches
Actuator Color:
Red single actuator
Actuator Inscription:
15 single actuator
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Rfi shielding
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes motor dc and 15.000 amperes inductive ac

NSN 5930-00-984-5352

Push Switch - Page 2 of 2



Thread Series Designator:
Un
Terminal Type And Quantity
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A053a0