NSN 5930-00-984-8593

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-984-8593

Hazardous Locations/environmental Protection:
Watertight
Actuator Length:
3.000 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.281 inches
Housing Height:
2.750 inches
Housing Length:
6.500 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.125 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.500 inches
Maximum Voltage Rating In Volts:
600.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
48.0 inch-ounces
Actuator Movement:
12.0 pretravel degrees and 37.0 overtravel degrees and 6.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
100.000 milliamperes resistive dc and 1.200 amperes resistive ac
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A053a0