## NSN 5930-00-984-9300

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-984-9300

Hazardous Locations/environmental Protection:				
Dustproof				
Overall Length:				
7.250 inches				
Overall Height:				
2.938 inches				
Overall Width:				
2.812 inches				
Unthreaded Mounting Hole Diameter:				
0.221 inches single mounting facility				
Individual Section Quantity:				
5				
Knob Manufacturer Code:				
82121				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Shortest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
2.188 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
2 each section periphery				
Throw Quantity:				
2 each section periphery				
Mounting Method:				
Bracket single mounting facility and unthreaded hole single mounting facility				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
500.0 highest ac voltage rating at sea level				
Switch Actuator Momentary Position:				
Clockwise single actuator				
Mounting Facility Pattern:				
Isosceles triangle single mounting facility				
Switch Actuator Indexing Position Quantity:				
2 single actuator				
Terminal Type:				
Tab w/screw				
Contact Switching Action:				

Contact Owncrining Action.

Breaks before makes each section periphery

## NSN 5930-00-984-9300

Rotary Switch - Page 2 of 2



Switch	Actuator	<b>Positioning</b>	Increment:

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0