

View Online at <https://aerobasegroup.com/nsn/5930-00-985-0430>

**Thread Class:**

2a 1st mounting facility

**Thread Length:**

0.297 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

8.405 inches

**Overall Height:**

2.750 inches

**Overall Width:**

2.625 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.515 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.172 inches 2nd mounting facility

**Individual Section Quantity:**

18

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches 2nd mounting facility

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing 1st mounting facility

**Thready Qty Per Inch (tpi):**

32 1st mounting facility

**Thread Size:**

0.469 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Uns 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0